

MATIC ULTRA L6

Liquid alkaline detergent for automatic dishwashers
in kitchen hygiene and the food industry

DESCRIPTION & APPLICATION

MATIC ULTRA L6 is a liquid highly effective alkaline non-foaming detergent for automatic dishwashers. **MATIC ULTRA L6** removes fat residues and dried food very well.

USE INSTRUCTIONS

MATIC ULTRA L6 is recommended to be dosed in an amount of 1 to 2 grams per 1 liter of water, depending on the degree of hardness of the water. The temperature and duration of action are given by the manufacturer of the automatic dishwasher. Rinse thoroughly after use and ensure that all product residues and soil particles are removed.

PRODUCT CHARACTERISTICS

Composition	Contains alkalines and sequestrants
Appearance	Cloudy liquid
Colour	Slightly yellow
Odour	Characteristic of the product
pH (100%)	13,5 ± 0,5
Density	± 1,205 g/cm ³ (20°C)
Solubility	Miscible in water in all proportions

MATERIAL COMPACTIBILITY

When **MATIC ULTRA L6** is used according to the recommended use instructions, then **MATIC ULTRA L6** can be used on materials commonly used in the food industry, with the exception of light alloys, galvanized material and soft metals as aluminum, copper, brass, rubber and similar materials.

ENVIRONMENT

The surfactants of **MATIC ULTRA L6** comply with the European Union Directive EU648/2004 on the biodegradability of surfactants.

SAFETY

Never mix **MATIC ULTRA L6** with other products. Carefully read the material safety data sheet of **MATIC ULTRA L6** and follow the chemical handling and disposal guidance.

STORAGE

Store **MATIC ULTRA L6** in its original packaging between 5°C and 30°C. Do not expose to direct sunlight. The expiry date is 24 months from date of manufacture.

PACKAGING

MATIC ULTRA L6 can be available in CANS and DRUM.

Technical Data Sheet **MATIC ULTRA L6**

Revision 29.05.2024